# Panasonic ideas for life

### **Split System Submittal Data**

Indoor: CS-S9NKUA Outdoor: CU-S9NKUA

Wall Mounted Air Conditioner's Low Ambient Models

Job Name: Location: Engineer:			
Submitted to:			
Submitted by: Reference:			
Neierence.			
Power		V/PH/Hz	230/208/1/60
Circuit Ampacity		(A)	15
Fuse Size, Max.		(A)	15
Compressor			DC Rotary Inverter
No. used		0.40	1
Output Power		(W)	700
Outdoor Unit	į		
Fan type			Propeller
Motor Type			DC Motor (8 poles)
Output Power		(W)	40
Airflow		CFM	1095
Coil Type			Aluminum (Blue Coated)
Fin Type - Pipe	Туре		Corrugated Fin
Rows - F.P.I			2 - 17
Face Area		(sq.ft)	3.8
Indoor Unit			
Fan type			Cross Flow
No. Speeds			5
RPM		(High)	1300
Motor Output		(W)	40
	(QLo/Lo/Me/H	łi/SHi)	191/230/311/395/434
Indoor Sound Ra	ating	(Hi) (dB-A)	40
Coil Type	_		Aluminum Fin & Copper Tube
Fin Type - Pipe	Гуре		Slit Plate - Inner Rifled
Rows - F.P.I		( 6)	2-17
Face Area	0:	(sq.ft)	2
Drain Connectio	n Size	(in.)	5/8"
Operating Rang	•		
		or Air Intake Temp.	Outdoor Air Intake Temp.
Cooling	Maximum	90F DB/74F WB	115F DB

		Pa	unasonic			
-	1					
ls						
	Approval					
	Date					
	Construction					
	Unit #					
	Drawing #	:				
8/1/60	Refrigerant				R410A	
15	Lbs R410a (	outdoor unit)			2.13	
15	Control			Electric Expansion Valve		
verter	Connection Line Length, Max (ft.)				Flare 66	
iverter 1	Lift Difference,	` '	49 (out	door lower), 49 (		
700	Line Size	` '	Discharge)	45 (	1/4"	
. 00	Line Size	,	. Suction)		3/8"	
peller	Dimensions	(in.)	Height	Width	Depth	
oles) 40	Indoor Unit	(Uncrated) (Crated)	11-7/16"	34-9/32"	8-1/16"	
1095	Outdoor Unit	(Uncrated) (Crated)	21-9/32"	30-23/32"	11-13/32"	
ated)						
ed Fin	Weight			Indoor	Outdoor	
2 - 17	Net		(lbs.)	20	82	
3.8	Shipping		(lbs.)			
		Data @ ARI Sta	ndard Condition	ns (230/208V)		
s Flow	Cooling		(DTLI/LI)		10200	
5 1300	Total Capacity SEER		(BTU/H)		10200 21	
40	SEER Dehumidification		(Pints/H)		1.3	
95/434	Amps		(A)		3.1	
40	Power Inputs		(W)		650	
			()		000	

#### **Features**


**Outdoor Sound Rating** 

Wireless Remote Controller Standard Wired Remote Controller ( CZ-RD516C ) Optional Microprocessor Remote ControllerLCD Wireless Type, Temp, Sensor Built In Temperature Control IC Thermostat Air Louver (Horizontal) Manual (Vertical) Automatic Power Failure Automatic Restart Built-In Self-Diagnosis Built-In Air Filter Washable, Anti-Mold

(dB-A)

47

## **Indoor Dimensions**



## **Outdoor Dimensions**

